

HP REGULATED TABLE

Surface Supplied MOD-1 Full Face Mask

DEPTH		50 RMV		RECOMMENDED 62.5 RMV		75 RMV	
FSW	MSW	PSIG	BAR	PSIG	BAR	PSIG	BAR
0 - 60	0 - 18	90 - 100	6.2 - 6.9	100 - 110	6.9 - 7.6	110 - 120	7.6 - 8.3
61 - 100	19 - 31	110 - 130	7.6 - 9.0	130 - 150	9.0 - 10.3	150 - 160	10.3 - 11.0
101 - 132	31 - 40	130 - 150	9.0 - 10.3	170 - 190	11.7 - 13.1	190 - 200	13.1 - 13.8
133 - 165	41 - 51	170 - 180	11.7 - 12.4	200 - 225	13.8 - 15.5	235 - 250	16.2 - 17.2
166 - 200	51 - 61	200 - 230	13.8 - 15.9	235 - 250	16.2 - 17.2	265 - 275	18.3 - 19.0

KM Diamond®

DEPTH		50 RMV		RECOMMENDED 62.5 RMV		75 RMV	
FSW	MSW	PSIG	BAR	PSIG	BAR	PSIG	BAR
0 - 60	0 - 18	90 - 120	6.2 - 8.3	90 - 130	6.2 - 9.0	110 - 140	7.6 - 9.7
61 - 100	19 - 31	110 - 130	7.6 - 9.0	120 - 140	8.3 - 9.7	140 - 160	9.7 - 11.0
101 - 132	31 - 40	130 - 150	9.0 - 10.3	160 - 180	11.0 - 12.4	180 - 200	12.4 - 13.8
133 - 165	41 - 51	155 - 185	10.7 - 12.8	180 - 220	12.4 - 15.2	235 - 250	16.2 - 17.2
166 - 200	51 - 61	190 - 220	13.1 - 15.2	220 - 250	15.2 - 17.2	255 - 275	17.6 - 19.0

SuperFlow®/SuperFlow® 350 Regulator

DEPTH		50 RMV		RECOMMENDED 62.5 RMV		75 RMV	
FSW	MSW	PSIG	BAR	PSIG	BAR	PSIG	BAR
0 - 60	0 - 18	90 - 120	6.2 - 8.3	100 - 120	6.9 - 8.3	115 - 140	7.9 - 9.7
61 - 100	19 - 31	115 - 140	7.9 - 9.7	140 - 160	9.7 - 11.0	160 - 190	11.0 - 13.1
101 - 132	31 - 40	140 - 160	9.7 - 11.0	170 - 200	11.7 - 13.8	210 - 230	14.5 - 15.9
133 - 165	41 - 51	170 - 190	11.7 - 13.1	200 - 220	13.8 - 15.2	240 - 260	16.5 - 17.9
166 - 200	51 - 61	210 - 230	14.5 - 15.9	235 - 255	16.2 - 17.6	-	0.0 - 0.0

455 Balanced Regulator

DEPTH		50 RMV		RECOMMENDED 62.5 RMV		75 RMV	
FSW	MSW	PSIG	BAR	PSIG	BAR	PSIG	BAR
0 - 60	0 - 18	90 - 110	6.2 - 7.6	90 - 110	6.2 - 7.6	100 - 120	6.9 - 8.3
61 - 100	19 - 31	110 - 130	7.6 - 9.0	130 - 150	9.0 - 10.3	150 - 170	10.3 - 11.7
101 - 132	31 - 40	130 - 150	9.0 - 10.3	160 - 180	11.0 - 12.4	190 - 210	13.1 - 14.5
133 - 165	41 - 51	160 - 180	11.0 - 12.4	180 - 210	12.4 - 14.5	220 - 245	15.2 - 16.9
166 - 200	51 - 61	190 - 220	13.1 - 15.2	225 - 250	15.5 - 17.2	260 - 280	17.9 - 19.3

HP REGULATED TABLE

REX® Regulator

DEPTH		50 RMV		RECOMMENDED 62.5 RMV		75 RMV	
FSW	MSW	PSIG	BAR	PSIG	BAR	PSIG	BAR
0 - 60	0 - 18	90 - 130	6.2 - 9.0	90 - 140	6.2 - 9.7	100 - 140	6.9 - 9.7
61 - 100	19 - 31	100 - 150	6.9 - 10.3	120 - 160	8.3 - 11.0	140 - 170	9.7 - 11.7
101 - 132	31 - 40	120 - 175	8.3 - 12.1	150 - 175	10.3 - 12.1	175 - 200	12.1 - 13.8
133 - 165	41 - 51	160 - 200	11.0 - 13.8	180 - 220	12.4 - 15.2	205 - 240	14.1 - 16.5
166 - 200	51 - 61	180 - 220	12.4 - 15.2	210 - 240	14.5 - 16.5	240 - 260	16.5 - 17.9

SuperFlow® 450 Regulator

DEPTH		50 RMV		RECOMMENDED 62.5 RMV		75 RMV	
FSW	MSW	PSIG	BAR	PSIG	BAR	PSIG	BAR
0 - 60	0 - 18	90 - 130	6.2 - 9.0	100 - 130	6.9 - 9.0	100 - 140	6.9 - 9.7
61 - 100	19 - 31	130 - 140	9.0 - 9.7	130 - 150	9.0 - 10.3	140 - 160	9.7 - 11.0
101 - 132	31 - 40	150 - 170	10.3 - 11.7	160 - 170	11.0 - 11.7	170 - 190	11.7 - 13.1
133 - 165	41 - 51	170 - 200	11.7 - 13.8	180 - 210	12.4 - 14.5	200 - 240	13.8 - 16.5
166 - 200	51 - 61	180 - 220	12.4 - 15.2	220 - 250	15.2 - 17.2	240 - 260	16.5 - 17.9